



Technical DataSheet

DynoWash™

Typical Physical Properties

Appearance...Clear / Blue-Green Liquid
Specific Gravity 0.950
Flash Point..... >152° F

Benefits & Applications

- Renders Iron Sulfide (black powder) less hazardous by mobilizing and encapsulating the particles, thus reducing their exposure to oxygen
- Product chemistry will de-oil and then encapsulate oil-wet solids into stable micelles, thus enabling easy removal with water
- Reduces the normal seawater displacement on pipeline abandonment requirements by as much as 300%

Packaging

DynoWash™ is available in 5-gallon (19-liter) pails and 55-gallon (208-liter) drums as a concentrate or can be shipped in transportable tote tanks for ready-to-pump applications.

Product Description

DynoWash™ is a micro-emulsion system with high solvency and high flash point characteristics. This environmentally friendly product removes difficult oil-wet solids from pipeline systems where encapsulation is critical for removal.

Treatment Recommendation

DynoWash™ can be provided as a ready-to-pump liquid blend or as a concentrate. The concentration range is dependent on the level of solids, oil and grease contamination. It is typically applied at 5% to 20% in aqueous solutions to produce effective cleaning spacers during pigging applications.

DISCLAIMER

This material is supplied solely for informational purposes. Production Improvement Consultants (PIC) makes no guarantees or warranties, either expressed or implied, with respect to the accuracy and use of the data.